

www.tilesbytina.com • 732.539.4655 • tserpico@tilesbytina.com

### ARKISTONE SERIES - Coloured Body Porcelain (Rectified)

# LIGHT (Light Grey) GRIEGE (Taupe) **IVORY** 30x60 cm (11.81"x23.622") 30x60 cm (11.81"x23.622") 30x60 cm (11.81"x23.622") Matte Finish Matte Finish Matte Finish 60x60 cm (23.622"x23.622") 60x60 cm (23.622"x23.622") 60x60 cm (23.622"x23.622") Matte Finish Matte Finish Matte Finish 60x120 cm (23.622"x47.208") 60x120 cm (23.622"x47.208") 60x120 cm (23.622"x47.208") Matte Finish Matte Finish Matte Finish



# ARKISTONE SERIES - Coloured Body Porcelain (Rectified)

#### **SILVER**



30x60 cm (11.81"x23.622") Matte Finish

60x60 cm (23.622"x23.622") Matte Finish

60x120 cm (23.622"x47.208") Matte Finish

### DARK (Dark Grey)



30x60 cm (11.81"x23.622") Matte Finish

60x60 cm (23.622"x23.622") Matte Finish

60x120 cm (23.622"x47.208") Matte Finish



# ARKISTONE SERIES - Coloured Body Porcelain (Rectified)






#### **ARKISTONE SERIES**

### **Tests Performed -- Results Conform**

Test	Standard Used	Min. Requirements	Results
Water Absorption	ISO 10545-3	< 0.5%	Conforms
Dynamic C.O.F.	ANSI A137.1-2012	≥ 0.42	Conforms
Slip Resistance	DIN 51130/51097	R-9	Conforms
Bending / Breaking Strength	ISO 10545-4	>1300N	Conforms
Modulus of Rupture	ISO 10545-4	≥ 35N/mm <sup>2</sup>	Conforms
Deep Abrasion Resistance	ISO 10545-6	≤ 175mm³	Conforms
Chemical Resistance	ISO 10545-13	min. UB	Conforms
Frost Resistance	ISO 10545-12	Required	Conforms
Stain Resistance	ISO 10545-14	> Class 3	Conforms

Technical data is supplied by the manufacturer and is subject to change at any time.

### **Colour Variation**



# **Examples of Recommended Applications**

Residential





Indoor







# **Packing Details**

TILE SIZE	PC/BOX	SF/BOX	LB/BOX	BOX/PAL
12" x 24" Tile (Matte) and 3-D Decor	7	13.56	57.33	40
24" x 24" Matte	3	11.54	47.37	40
24" x 48" Matte	2	15.50	65.70	35





### **Recommended FLEXTILE Installation Systems**

For other suitable options & complete installation details, visit www.flextile.net

PRODUCT	WALL APPLICATION		FLOOR APPLICATION	
	Interior	Exterior	Interior	Exterior
TILE BOND COAT	• 66 FlexLite • 56SR LHT Mortar	• 5400 Maxi-Flex • 51/44 Latex Mortar System	• 56SR LHT Mortar • 61 Full Coverage Mortar	• 5400 Maxi-Flex • 51/44 Latex Mortar System
GROUT	<ul><li>500 PM Unsanded</li><li>600 PM Sanded</li><li>ColourMax Plus Quartz</li></ul>	• 600 PM Sanded • 1600 PM Sanded	<ul><li>600/1600 PM Sanded</li><li>FlexEpoxy 100 Epoxy</li></ul>	• 600 PM Sanded • 1600 PM Sanded
CAULKING	Ultra Performance (colour-matched to grout)	Ultra Performance (colour-matched to grout)	Ultra Performance (colour-matched to grout)	Ultra Performance (colour-matched to grout)

#### **SURFACE PREPARATION (If Required)**

- Floor levelling: 59 Flex Flo / 5900 Flex Flo Plus Self Levelling Underlayment
- · Waterproofing: WP900 Waterproof Membrane
- Crack Isolation/Uncoupling: Flexilastic 1000 Crack Isolation Membrane / FlexMat Uncoupling Membrane

<sup>\*</sup> For a complete listing of FLEXTILE products and accessories including Sound Control, In-Floor Heating, and further setting options, please visit www.flextile.net



# "MORE" Surface Care Product Guide


Task	Product Recommendation	Dilution with Water	Frequency
Grout Sealing	MORE™ Grout, Ceramic & Porcelain Sealer	Ready to use	Commercial: 1-3 Years Residential: 5-8 Years
Daily Maintenance	MORE™ Stone and Tile Cleaner	1 : 128 Ratio	Daily
Deep Cleaning	MORE™ Alkaline Cleaner	1 : 4 Ratio	As Needed
Grout Haze- Cementitious	MORE™ Acidic Cleaner	1 : 4 Ratio	As Needed
Grout Haze - Epoxy / Urethane	MORE™ Coating Stripper*	Ready to use	As Needed

<sup>\*</sup> Always test in an inconspicuous area to make sure the product is achieving the desired results and is not damaging the finish of the surface.





LIGHT (Light Grey)




DARK (Dark Grey)





**IVORY** 



LIGHT (Light Grey) Decor

