

Victoria Series  
**LIVING**  
Series

**GLAZED PORCELAIN**



TILES BY TINA

[www.tilesbytina.com](http://www.tilesbytina.com) • 732.539.4655 • [tserpico@tilesbytina.com](mailto:tserpico@tilesbytina.com)

# Living Series - Glazed Porcelain

BIANCO (White)

TORTORA (Warm Grey)

NOCE (Brown)



7.5 x 45 cm (3 x 18)

7.5 x 45 cm (3 x 18)

7.5 x 45 cm (3 x 18)

# Living Series - Glazed Porcelain

CENERE (Anthracite)

NERO (Black)



7.5 x 45 cm (3 x 18)

7.5 x 45 cm (3 x 18)

## LIVING SERIES

## Tests Performed -- Results Conform

Test	Standard Used	Min. Requirements	Results
Water Absorption	ISO 10545-3	< 0.5%	Conforms
Slip Resistance	DIN 51130	> R9	Conforms
Dynamic C.O.F.	ANSI A137.1-2012	≥ 0.42	Conforms
Bending / Breaking Strength	ISO 10545-4	>1300N	Conforms
Scratch Hardness	MOHs Scale	-	MOHs 7
Chemical Resistance	ISO 10545-13	min. UB	Conforms
Frost Resistance	ISO 10545-12	Required	Conforms
Visible Surface Abrasion Resistance	ISO 10545-7	-	PEI-5
Stain Resistance	ISO 10545-14	> Class 3	Conforms

Technical data is supplied by the manufacturer and is subject to change at any time.

## Colour Variation



## Examples of Recommended Applications



## Packing Details

TILE SIZE	PC/BOX	SF/BOX	LB/BOX	BOX/PAL
3" x 18"	26	9.69	40.04	42



TILES BY TINA  
www.tilesbytina.com

## Recommended FLEX TILE Installation Systems

For other suitable options & complete installation details, visit [www.flextile.net](http://www.flextile.net)

PRODUCT	WALL APPLICATION		FLOOR APPLICATION	
	Interior	Exterior	Interior	Exterior
TILE BOND COAT	<ul style="list-style-type: none"> <li>• 56SR Full Coverage LHT</li> <li>• 66 FlexLite</li> </ul>	<ul style="list-style-type: none"> <li>• 5400 Maxi-Flex</li> <li>• 51/44 Latex Mortar System</li> </ul>	<ul style="list-style-type: none"> <li>• 52 Versatile</li> <li>• 56SR Full Coverage LHT</li> </ul>	<ul style="list-style-type: none"> <li>• 5400 Maxi-Flex</li> <li>• 51/44 Latex Mortar System</li> </ul>
GROUT	<ul style="list-style-type: none"> <li>• 500 PM Unsanded</li> <li>• 600 PM Sanded</li> <li>• ColourMax Plus Quartz</li> </ul>	<ul style="list-style-type: none"> <li>• 600 PM Sanded</li> <li>• 1600 Fast Setting</li> </ul>	<ul style="list-style-type: none"> <li>• 600 PM Sanded</li> <li>• FlexEpoxy 100 Epoxy</li> </ul>	<ul style="list-style-type: none"> <li>• 600 PM Sanded</li> <li>• 1600 RSG Fast Set</li> </ul>
CAULKING	Ultra Performance Hybrid Caulk (colour-matched to grout)	Ultra Performance Hybrid Caulk (colour-matched to grout)	Ultra Performance Hybrid Caulk (colour-matched to grout)	Ultra Performance Hybrid Caulk (colour-matched to grout)

### SURFACE PREPARATION (If Required)

- **Floor levelling:** 59 Flex Flo / 5900 Flex Flo Plus Self Levelling Underlayment
- **Waterproofing:** WP900 Waterproof Membrane
- **Crack Isolation/Uncoupling:** Flexilastic 1000 Crack Isolation Membrane / FlexMat Uncoupling Membrane

\*For a complete listing of FLEX TILE products and accessories including Sound Control, In-Floor Heating, and further setting options, please visit [www.flextile.net](http://www.flextile.net)



## "MORE" Surface Care Product Guide

Task	Product Recommendation	Dilution with Water	Frequency
Grout Sealing	MORE™ Grout, Ceramic & Porcelain Sealer	Ready to use	Commercial: 1-3 Years Residential: 5-8 Years
Daily Maintenance	MORE™ Stone and Tile Cleaner	1 : 128 Ratio	Daily
Deep Cleaning	MORE™ Alkaline Cleaner	1 : 4 Ratio	As Needed
Grout Haze- Cementitious	MORE™ Acidic Cleaner	1 : 4 Ratio	As Needed
Grout Haze - Epoxy / Urethane	MORE™ Coating Stripper*	Ready to use	As Needed

\*Always test in an inconspicuous area to make sure the product is achieving the desired results and is not damaging the finish of the surface.



**TORTORA (Warm Grey)**



**NERO (Black)**



TILES BY TINA  
[www.tilesbytina.com](http://www.tilesbytina.com)



NOCE (Brown)