

www.tilesbytina.com • 732.539.4655 • tserpico@tilesbytina.com

ORO SERIES - Coloured Body Porcelain (Rectified)



CREMA AVORIO60 x 60 cm (24" x 24") Matte
60 x 60 cm (24" x 24") Polished
60 x 120 cm (24" x 48") Polished



OCEAN BLUE 60 x 60 cm (24" x 24") Matte 60 x 60 cm (24" x 24") Polished 60 x 120 cm (24" x 48") Polished




AGATA DP BLUE 60 x 60 cm (24" x 24") Matte 60 x 60 cm (24" x 24") Polished 60 x 120 cm (24" x 48") Polished



ILLUSION BRONZE 60 x 60 cm (24" x 24") Matte 60 x 60 cm (24" x 24") Polished 60 x 120 cm (24" x 48") Polished



TERRA SERIES - Coloured Body Porcelain (Rectified)



ARGENTO (Light Grey) 60 x 60 cm (24" x 24") Matte



BLU DI PRUSSIA (Blue/Grey) 60 x 60 cm (24" x 24") Matte



ORO & TERRA SERIES

Tests Performed -- Results Conform

Test	Standard Used	Min. Requirements	Results
Water Absorption	ISO 10545-3	≤ 0.5%	Conforms
Bending / Breaking Strength	ISO 10545-4	> 1300N	Conforms
Modulus of Rupture	ISO 10545-4	> 35N/mm ²	Conforms
Dynamic C.O.F.	ANSI A137.1/2012	> 0.42	Conforms
Deep Abrasion Resistance	ISO 10545-6	≤ 175 mm³	Conforms
Chemical Resistance	ISO 10545-13	min. UB	Conforms
Frost Resistance	ISO 10545-12	Required	Conforms
Stain Resistance	ISO 10545-14	> Class 3	Conforms

Technical data is supplied by the manufacturer and is subject to change at any time.

Colour Variation



Examples of Recommended Applications

Residential





Indoor



Outdoor



Wall





Packing Details

TILE SIZE	PC/BOX	SF/BOX	LB/BOX	BOX/PAL
24" x 24" Matte & Polished	3	11.62	54.24	40
24" x 48" Polished	2	15.50	72.74	30





Recommended FLEXTILE Installation Systems

For other suitable options & complete installation details, visit www.flextile.net

PRODUCT	WALL APPLICATION		FLOOR APPLICATION	
	Interior	Exterior	Interior	Exterior
TILE BOND COAT	• 66 FlexLite Pm Mortar • 56SR LHT Mortar	• 5400 Maxi-Flex • 51/44 Latex Mortar System	• 61 Full Coverage Mortar • 56SR LHT Mortar	• 5400 Maxi-Flex • 51/44 Latex Mortar System
GROUT	500 PM Unsanded Grout600 PM Sanded Grout1600UPG PM Grout	• 600 PM Sanded Grout • 1600UPG PM Grout	• 600 PM Sanded Grout • 1600UPG PM Grout • FlexEpoxy 100 Epoxy Grout	• 600 PM Sanded Grout • 1600UPG PM Grout
CAULKING	Ultra Performance (colour-matched to grout)	Ultra Performance (colour-matched to grout)	Ultra Performance (colour-matched to grout)	Ultra Performance (colour-matched to grout)

SURFACE PREPARATION (If Required)

- Floor levelling: 59 Flex Flo / 5900 Flex Flo Plus Self Levelling Underlayment
- · Waterproofing: WP900 Waterproof Membrane
- · Crack Isolation/Uncoupling: Flexilastic 1000 Crack Isolation Membrane / FlexMat Uncoupling Membrane

^{*} For a complete listing of FLEXTILE products and accessories including Sound Control, In-Floor Heating, and further setting options, please visit www.flextile.net



"MORE" Surface Care Product Guide

Task	Product Recommendation	Dilution with Water	Frequency
Grout Sealing	MORE™ Grout, Ceramic & Porcelain Sealer	Ready to use	Commercial: 1-3 Years Residential: 5-8 Years
Daily Maintenance	MORE™ Stone and Tile Cleaner	1 : 128 Ratio	Daily
Deep Cleaning	MORE™ Alkaline Cleaner	1 : 4 Ratio	As Needed
Grout Haze- Cementitious	MORE™ Acidic Cleaner	1 : 4 Ratio	As Needed
Grout Haze - Epoxy / Urethane	MORE™ Coating Stripper*	Ready to use	As Needed

^{*}Always test in an inconspicuous area to make sure the product is achieving the desired results and is not damaging the finish of the surface.





ORO - Agata DP Blue



ORO - Ocean Blue





ORO - Illusion Bronze



ORO - Crema Avorio





