

Victoria Series VETRI Series

GLAZED PORCELAIN



TILES BY TINA

www.tilesbytina.com • 732.539.4655 • tserpico@tilesbytina.com

VETRI SERIES - Glazed Porcelain (Rectified)



BIANCO (White) Polished

60 x 60 cm (23.622" x 23.622")

30 x 60 cm (11.811" x 23.622")

20 x 60 cm (7.87" x 23.622")



NATURAL (Grey/Blue) Polished

60 x 60 cm (23.622" x 23.622")

30 x 60 cm (11.811" x 23.622")

20 x 60 cm (7.87" x 23.622")



VETRI SERIES - Glazed Porcelain (Rectified)



BRONZO (Taupe) Polished

60 x 60 cm (23.622" x 23.622")

30 x 60 cm (11.811" x 23.622")

20 x 60 cm (7.87" x 23.622")



FUME (Grey) Polished

60 x 60 cm (23.622" x 23.622")

30 x 60 cm (11.811" x 23.622")

20 x 60 cm (7.87" x 23.622")



VETRI SERIES GLAZED PORCELAIN

Tests Performed -- Results Conform

Test	Standard Used	Min. Requirements	Results
Water Absorption	ISO 10545-3	< 0.5%	Conforms
Bending/Breaking Strength	ISO 10545-4	> 1300N	Conforms
Deep Abrasion Resistance	ISO 10545-6	≤ 175mm ³	Conforms
Chemical Resistance	ISO 10545-13	min. UB	Conforms
Frost Resistance	ISO 10545-12	Required	Conforms
Visible Surface Abrasion Resistance	ISO 10545-7	PEI-4	Conforms
Stain Resistance	ISO 10545-14	> Class 3	Conforms

Technical data is supplied by the manufacturer and is subject to change at any time.

Colour Variation



Examples of Recommended Applications

Residential



Commercial



Indoor



Outdoor



Wall



Floor*



*Residential and low-traffic commercial floors only.

Packing Details

TILE SIZE	PC/BOX	SF/BOX	LB/BOX	BOX/PAL
24" x 24" Polished	3	11.63	47.07	40
12" x 24" Polished	7	13.56	55.09	40
8" x 24" Polished	7	9.04	40.11	48



TILES BY TINA
www.tilesbytina.com

PRODUCT	WALL APPLICATION		FLOOR APPLICATION	
	Interior	Exterior	Interior	Exterior
TILE BOND COAT	<ul style="list-style-type: none"> • 66 FlexLite • 56SR LHT Mortar 	<ul style="list-style-type: none"> • 5400 Maxi-Flex • 51/44 Latex Mortar System 	<ul style="list-style-type: none"> • 61 LFT Mortar • 56SR LHT Mortar 	n/a
GROUT	<ul style="list-style-type: none"> • 500 PM Unsanded • 1600 Grout 	<ul style="list-style-type: none"> • 1600 Grout 	<ul style="list-style-type: none"> • 600 PM Unsanded • 1600 Grout 	n/a
CAULKING	Ultra Performance (colour-matched to grout)	Ultra Performance (colour-matched to grout)	Ultra Performance (colour-matched to grout)	n/a

SURFACE PREPARATION (If Required)

- Floor levelling: 59 Flex Flo / 5900 Flex Flo Plus Self Levelling Underlayment
- Waterproofing: WP900 Waterproof Membrane
- Crack Isolation/Uncoupling: Flexilastic 1000 Crack Isolation Membrane / FlexMat Uncoupling Membrane

* For a complete listing of FLEX TILE products and accessories including Sound Control, In-Floor Heating, and further setting options, please visit www.flextile.net



“MORE” Surface Care Product Guide

Task	Product Recommendation	Dilution with Water	Frequency
Grout Sealing	MORE™ Grout, Ceramic & Porcelain Sealer	Ready to use	Commercial: 1-3 Years Residential: 5-8 Years
Daily Maintenance	MORE™ Stone and Tile Cleaner	1 : 128 Ratio	Daily
Deep Cleaning	MORE™ Alkaline Cleaner	1 : 4 Ratio	As Needed
Grout Haze- Cementitious	MORE™ Acidic Cleaner	1 : 4 Ratio	As Needed
Grout Haze - Epoxy / Urethane	MORE™ Coating Stripper*	Ready to use	As Needed

* Always test in an inconspicuous area to make sure the product is achieving the desired results and is not damaging the finish of the surface.





NATURAL (Grey/Blue)



TILES BY TINA
www.tilesbytina.com