



Roberto Series **Pro** Porcelain



TILES BY TINA

www.tilesbytina.com

732.539.4655

tserpico@tilesbytina.com



PORCELAIN

Roberto Series

Pro Porcelain

Basic and essential. This sums up the Pro series, which comes in an array of neutral colors that are practical to use and easy to maintain in any type of space.

Pro Sand 35"x35" R PO

2 | Pro



Glazed & Polished Porcelain

◇ 35"x35" R - 24"x48" R - 24"x24" R - 12"x24" R - 3x12"

Pro | 3



Pro Cement 24"x24" R UP



Pro Ivory 24"x24" R UP



8.5-10 |
 |
 35"x35" 24"x48" R 24"x24" R 12"x24" R 3"x12"
 90x90 cm 60x120 cm 60x60 cm 30x60 cm 7.5x30 cm

Ivory



35"x35" R
UP
PO:



24"x48" R
UP
PO:



24"x24" R
UP
PO:



12"x24" R
UP
PO:



13"x13" Mosaic



3"x12"



3"x12" Bullnose

Nude



35"x35" R
UP
PO:



24"x48" R
UP
PO:



24"x24" R
UP
PO:



12"x24" R
UP
PO:



13"x13" Mosaic



3"x12"



3"x12" Bullnose

Sand



35"x35" R
UP
PO:



24"x48" R
UP
PC



24"x24" R
UP
PO:



12"x24" R
UP
PO

Cement



35"x35" R
UP
PO:



24"x48" R
UP
PO:



24"x24" R
UP
PO:



12"x24" R
UP
PO:



13"x13" Mosaic



3"x12"



3"x12" Bullnose

Pro

Glazed & Polished Porcelain

8.5-10 mm | | **P** **M** | **35"x35" R** 90x90 cm | **24"x48" R** 60x120 cm | **24"x24" R** 60x60 cm | **12"x24" R** 30x60 cm | **3"x12"** 7.5x30 cm



Concrete



35"x35" R
UP:
PO:



24"x48" R
UP:
PO:



24"x24" R
UP:
PO:



12"x24" R
UP:
PO:



13"x13" Mosaic



3"x12"



3"x12" Bullnose



TILES BY TINA
www.tilesbytina.com

Pro Concrete 24"x48" R UP

Pro

Glazed & Polished Porcelain

Technical Specifications

| CHARACTERISTICS | STANDARD | DECLARED ASTM | |
|--|-------------|---------------|------------|
| | | Polished | Unpolished |
| Water Absorption | C373 | <=0.5% | <=0.5% |
| Break Strength | C648 | Min. 335 | Min. 335 |
| Scratch Hardness | MOH's Scale | 3 | 5 |
| Chemical Resistance | C650 | Unaffected | Unaffected |
| Frost Resistance | C1026 | Resistant | Resistant |
| Group | See FAQ's | 3 | 4 |
| Deep Abrasion - Unglazed Tiles | C1243 | Pass | Pass |
| PEI- Glazed Tiles*** | C1027 | 3 | - |
| Minimum Bond Strength (PSI) | C482 | 165 | 165 |
| Dynamic Coefficient of Friction (DCOF) | A137.1 | <=0.40 | >=0.42 |
| Shade and Texture Rating | CTDA "V" | V3 | V3 |
| Facial Dimensions | C499 | Pass | Pass |
| Range of Thickness | C499 | Pass | Pass |
| Warpage | C485 | Pass | Pass |
| Wedging | C502 | Pass | Pass |

Packaging Info

| Size | SF per carton | PC per carton |
|-----------------|---------------|---------------|
| 3"x12" | 10.98 | 46 |
| 12"x24" | 18.94 | 10 |
| 24"x24" PO | 19.05 | 5 |
| 24"x24" UP | 23.25 | 6 |
| 35"x35" | 17.22 | 2 |
| 24"x48" | 15.28 | 2 |
| 13"x13" Mosaic | 13.15 | 11 |
| 3"x12" Bullnose | 5.92 | 24 |



TILES BY TINA
www.tilesbytina.com